

ZT231 Industrial Printer

Smart features. Small investment. Big payoff.

Demands are rising and timelines are shrinking. Do you have the printing capabilities to keep up – without interruption? The ZT231 delivers the right combination of the right features at the right price, along with the long-lasting quality you expect from Zebra. Fast print speeds, high-resolution print quality, large color touchscreen, future-forward design and more – in one space-saving footprint. Plus, add optional capabilities like RFID, wireless connectivity and media handling features when you need them. But that's not all. Get built-in intelligence to make your work easier, and high security to help you along the way. That's how Zebra defines value.



Get More Value with Zebra

Simple Operation with Smart Features

Reduce training time with the ZT231's easy-to-use 4.3" full-color touchscreen. See status at a glance, access wizards and helpful how-to videos and make changes with the touch of a finger or gloved hand. Smoothly integrate the ZT231 into your existing network as it is backwards compatible and features Printer Emulations to replace other brands without having to change label formats or rewrite code.

Make It Easy for Your IT Team

Take advantage of Zebra's robust, ever growing Print DNA software suite for added capabilities. Easily configure, troubleshoot and manage your printers onsite or remotely via a web-based dashboard. Compare your printer security settings against practice preferences and adjust to match them, while protecting your data from vulnerabilities.

The Smart Choice Now and Later

The benefits of buying a ZT231 don't end at the point of purchase. Expand your printer's capabilities with field-installable upgrades when you need them. Add options such as a cutter or peeler, wireless connectivity or even UHF RFID encoding.

Built to Perform. Engineered to Endure.

Don't Compromise on Quality

With a durable metal frame, the ZT231 is ideal for light industrial environments. Print crisp text and barcodes with optional 300 dpi resolution. Advance your label throughput with fast print speeds up to 12 ips at 203 dpi. Be confident knowing you're backed by Zebra, a high performer in barcode printing.

Expect more. More value. More features. More for your budget.

For more information, please visit www.zebra.com/zt231

Get More Done with Greater Visibility

The ZT231 includes an outstanding architecture to process more jobs at once and evolve with emerging technologies. Onboard analytics and printhead element out detection help you plan maintenance in advance. And, the easy tool-less platen and print head removal makes maintenance easy.

Small Footprint, Great Outcome

To help you make good use of your workspace, we've engineered the ZT231 with a space-saving, compact design and bi-fold door that reduces the height needed to open your printer. Take the trouble out of media loading with an intuitive design and color-coded cues. Adjustable sensors offer greater media flexibility and the large ribbon roll capacity lets you change media less frequently.

Connect Your Way

Take advantage of a variety of standard connectivity options including USB, Serial, Ethernet and USB Host. Tap to pair and print with compatible mobile devices with the Print Touch tag (NFC). Add a second Ethernet port, 802.11ac or an Applicator port.

Get RFID Without Complication

Incorporate UHF RFID printing and encoding* for greater visibility and tracking. Get greater media flexibility and simple RFID calibration with Zebra's adaptive encoding technology that reduces complex placement guidelines.

Software That Gives You a Serious Advantage

Update, Troubleshoot and Monitor – from a Single Location

With Zebra's Printer Profile Manager Enterprise, part of Print DNA, you can easily manage, secure and troubleshoot your networked printers from nearly any location. And an intuitive browser-based interface lets you see status at a glance, quickly triage issues to reduce downtime and perform updates and maintenance.

Peace-of-Mind Printer Security

Security risks are real and costly. Endpoints are becoming popular targets – including networked thermal printers. Shield yourself from cyber attacks with Zebra's PrintSecure, part of Print DNA. Easily configure your printers via secure connections, identify vulnerabilities, block unauthorized access and detect events before they happen.

Supplies, Service and Support

Zebra Certified Supplies

Printing supplies provide a digital voice for assets across your supply chain. You rely on them to disseminate critical data throughout your organization. If something goes wrong with your printing supplies, operations are interrupted, productivity suffers and costs rise. That's why we design, produce and rigorously pretest our own line of labels and tags to ensure consistent, optimized performance in your Zebra printer. For good quality, service and thermal printing expertise, choose Zebra Certified Supplies.

Backed by Zebra's Worldwide Service and Support

Access repair support services around the globe through Zebra and its trusted network of more than 10,000 partners. Zebra OneCare™ Maintenance Plans provide enhanced coverage that exceeds standard warranty.

Specifications

Standard Features

• Print methods: direct-thermal or thermal-transfer • Construction: metal frame and metal enclosures • Bi-fold media door with large clear window • Side-loading supplies path for simplified media and ribbon loading • Thin film printhead with E3™ Element Energy™ Equalizer for good print quality • Three-color LEDs for quick printer status • 4.3" color resistive touch screen with intuitive menu for quick operation and settings • Communications: USB 2.0, RS-232 Serial port, 10/100 Ethernet, and USB Host • ENERGY STAR™ certified • Bluetooth Low Energy (BTLE) technology for enhanced location precision • ZebraDesigner Essentials – easy label design tool free at www.zebra.com/zebradesigner • Real-Time Clock (RTC)

Physical Characteristics

Dimensions*	ZT231 Closed: 17 in. L x 9.5 in. W x 11 in. H 432 mm L x 241 mm W x 279 mm H ZT231 with Liner Takeup Unit: 17 in. L x 9.5 in. W x 12.75 in. H 432 mm L x 241 mm W x 324 mm H
Weight	ZT231: 20 lbs./9.1 kg ZT231 with Liner Takeup Unit: 24 lbs./10.9 kg
	*Dimensions are for the base model printer. Consult your salesrepresentative for specifics regarding other configurations.

Printer Specifications

Resolution	203 dpi/8 dots per mm 300 dpi/12 dots per mm (optional)
Memory	256 MB SDRAM memory 256 MB on-board linear Flash memory
Maximum Print Width	4.09 in./104 mm
Maximum Print Speed	12 ips (203 dpi) 8 ips (300 dpi)
Media Sensors	Moveable transmissive and reflective sensors
Maximum Print Length	203 dpi: 157 in/3988 mm 300 dpi: 73in/1854 mm

Media Characteristics

Minimum Label and Liner Length	Tear mode: 0.7 in/18 mm Cutter mode: 1 in/25 mm Peel mode: 0.5 in/13 mm
Media Width	0.75 in./19.4 mm to 4.50 in./114 mm
Media Roll Size	8.0 in./203 mm O.D. on a 3.0 in./76 mm I.D. core 6.0 in./152 mm O.D. on a 1.0 in./25 mm I.D. core
Media Thickness	0.003 in./0.076 mm to 0.010 in./0.25 mm
Media Types	Continuous, die-cut, notch, black mark

Firmware

ZBI 2.0™ — Optional powerful programming language that lets printers run stand-alone applications, connect to peripherals, and much more. ZPL and ZPL II™ — Zebra Programming Language provides sophisticated label formatting and printer control and is compatible with Zebra printers. EPL and EPL2™ — Eltron Programming Language simplifies label formatting and enables format compatibility with legacy applications. (EPL available on 203 dpi models only.)
--

Barcode Symbolologies

Linear Barcodes: Code 11, Code 39, Code 93, Code 128 with subsets A/B/C and UCC Case Codes, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN with 2 or 5 digit extensions, Plessey, Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar, Planet Code 2D Barcodes: Aztec, Codablock, PDF417, Code 49, Data Matrix, MaxiCode, QR Code, MicroPDF417, TLC 39, RSS-14 (and composite)
--

Fonts and Graphics

Z7 bitmapped, 1 smooth-scalable (CG Triumvirate™ Bold Condensed) Pre-loaded Unicode™-compliant scalable fonts for EMEA character sets International character sets supporting the following code page: IBM™ Code Page 850 Supports user-defined fonts and graphics, including custom logos ZPL II drawing commands including boxes and lines 64 MB user available Flash memory storage for downloadable objects; 32 MB user-available SDRAM

Options and Accessories

Communication • 802.11ac Wi-Fi option card • 10/100 Ethernet option card • Applicator Interface Media Handling • Peel — a front-mount, passive-peel with no take-up spindle • Peel — a front-mount, passive-peel with liner take-up spindle (factory-fit only) • Cutter — a front-mount guillotine cutter RFID • UHF field-installable RFID kit Keyboard Display Unit • ZKDU™ keyboard display units for stand-alone printing applications
--

Managed Print Services (MPS) Made Simple

Our printers offer advanced remote management, analytics and security capabilities that make them the obvious choice for MPS. With the Print DNA software suite, your Zebra MPS provider can remotely manage and optimize your printers, track and automate supplies replenishment and ensure security. For more information, please visit www.zebra.com/managed-print-services

Markets and Applications

Manufacturing

- Work-in-process
- Product ID/serial numbers
- Packaging labeling
- Receiving/put-away labeling

Transportation and Logistics

- Order picking/packing
- Shipping/receiving
- Cross-docking
- Compliance labeling

Healthcare

- Laboratory labeling
- Blood bank labeling
- Asset tracking
- Unit-dose labeling
- Pharmacy labeling

Retail

- Buy online pick up in store labeling
- Return tagging
- Price labeling
- Shipping labeling

Ribbon Characteristics (Thermal-transfer option only)

Standard Length	1,476 ft./450 m
Width	2 in./51 mm to 4.33 in./110 mm
Core	1.0 in./25.4 mm

Operating Characteristics

Operating Temp.	Thermal transfer: 40°F to 105°F/5° to 40°C Direct thermal: 32°F to 105°F/0° to 40°C
Storage/Transportation Temperature	-40°F to 140°F/-40° to 60°C
Operating Humidity	20% to 85% non-condensing
Storage Humidity	5% to 85% non-condensing
Electrical	Universal auto-ranging (PFC-compliant) power supply 100-240 VAC; 50-60 Hz ENERGY STAR certified
Agency Approvals	IEC 62368-1, EN55022 Class B, EN55024, EN55035, EN61000-3-2, EN61000-3-3, FCC Class B, ICES-003, FCC 15.209; 15.247(d), IC RSS 247, EN 300 328, EN 301 893, EN 62311, cTUVus, CE Marking, UKCA, VCCI, RCM, S-Mark, CCC, CU EAC, BSMI, KCC, and BIS

Print DNA Software

This printer is supported by our Print DNA suite of software capabilities to get your printer up and running quickly and securely, and enable your printer to evolve with your business needs. Print DNA features may vary by model, and some features may require a license.
For more information, please visit www.zebra.com/printdna

了解更多产品和行业应用: www.zebra.com

斑马技术销售支持热线: 4009201899

(注: 如果您是铁通用户, 请发邮件至contact.apac@zebra.com咨询)

	上海 上海市静安区石门一路 288 号 兴业太古汇香港兴业中心二座 2801 & 2807 – 2812 200040 电话: +86 21 6010 2222 传真: +86 21 6288 8393	北京 北京市东城区北三环东路 36 号环球贸易中心 D 座 1203-1206 室 100013 电话: +86 10 5662 2000 传真: +86 10 5825 7426	广州 广州市林和西路 9 号 耀中广场 B3412-3415 室 510610 电话: +86 20 3810 7798 传真: +86 20 3810 7783	成都 成都市高新区交子大道 177 号中海国际中心 B 座 1511 室 610041 电话: +86 28 8333 7630 传真: +86 28 8556 6582	南京 南京市鼓楼区汉中路 2 号 金陵饭店亚太商务楼 8 楼 871 室 210005 电话: +86 25 6610 2619 传真: +86 25 6610 2619	武汉 武汉市武昌区中南路 7 号 中商广场写字楼 A 座 1817 室 430071 电话: +86 27 8773 7490 传真: +86 27 8773 7493	深圳 广东省深圳市福田区中心 四路一号嘉里建设广场 第一座1704室 518048 电话: +86 755 3305 3911 传真: +86 755 3651 3950	香港 香港九龙尖沙咀 广东道 30 号 新港中心 2 座 911 室 电话: +852 3622 2271 传真: +852 2157 0333	台北 台北市信义区松高路9号 统一国际大楼13楼 110 电话: +886 2 87299300 传真: +886 2 87299388
---	---	--	---	---	---	--	---	--	--